



Formula Series

5,5 to 30 kW



Fixed speed



| Type | kW | HP | l/min | cfm | l/min | cfm | l/min | cfm | dB(A) | L x W x H (mm) | Kg |
|-----------|------|-----|-------|-------|-------|-------|-------|-------|-------|-------------------|-----|
| Formula | 5,5 | 7,5 | 820 | 28,9 | 670 | 23,7 | 520 | 18,4 | 66 | 1095 x 620 x 1070 | 235 |
| Formula E | | | | | | | | | | | 265 |
| Formula | 7,5 | 10 | 1153 | 40,7 | 1000 | 35,3 | 810 | 28,6 | 66 | 1095 x 620 x 1070 | 240 |
| Formula E | | | | | | | | | | | 270 |
| Formula | 11 | 15 | 1665 | 58,8 | 1435 | 50,7 | 1210 | 42,7 | 69 | 1095 x 620 x 1070 | 260 |
| Formula E | | | | | | | | | | | 290 |
| Formula | 15 | 20 | 1985 | 70,1 | 1771 | 62,5 | 1480 | 52,2 | 69 | 1095 x 620 x 1070 | 285 |
| Formula E | | | | | | | | | | | 315 |
| Formula | 15 | 20 | 2218 | 78,3 | 2020 | 71,3 | 1538 | 54,3 | 70 | 1095 x 620 x 1070 | 315 |
| Formula E | | | | | | | | | | | 345 |
| Formula | 18,5 | 25 | 2767 | 97,7 | 2567 | 90,6 | 2017 | 71,2 | 72 | 1204 x 786 x 1220 | 375 |
| Formula E | | | | | | | | | | 1659 x 786 x 1220 | 448 |
| Formula | 22 | 30 | 3417 | 120,6 | 3017 | 106,5 | 2417 | 85,3 | 74 | 1204 x 786 x 1220 | 391 |
| Formula E | | | | | | | | | | 1659 x 786 x 1220 | 464 |
| Formula | 30 | 40 | 3783 | 133,5 | 3367 | 118,9 | 2833 | 100,0 | 77 | 1204 x 786 x 1220 | 419 |

Variable Speed



Min



Max



| Type | kW | HP | Bar | l/min | cfm | l/min | cfm | dB(A) | L x W x H (mm) | Kg |
|------------|----|----|--------|-------|------|--------|-------|-------|-------------------|-----|
| Formula I | 11 | 15 | 6 - 13 | 425 | 15,0 | 1621,2 | 57,2 | 73 | 1095 x 620 x 1095 | 305 |
| Formula IE | | | | | | | | | | 335 |
| Formula I | 22 | 30 | 4 - 10 | 645 | 22,8 | 3666 | 129,4 | 74 | 1204 x 786 x 1220 | 419 |
| Formula IE | | | | | | | | | 1659 x 786 x 1220 | 492 |
| Formula I | 22 | 30 | 7 - 13 | 675 | 23,8 | 3216 | 113,5 | 74 | 1204 x 786 x 1220 | 419 |
| Formula IE | | | | | | | | | 1659 x 786 x 1220 | 492 |

* Unit performance measured according to ISO 1217. Noise level measured according to ISO 2151. Reference conditions: instake air pressure 1bar, 20°C and 70% UR.