

ABAC ZERO

The Oil-free Air Compressor





The Oil-free Air Compressor

ABAC ZERO



Protecting the environment and your business has never been easier

The new ABAC ZERO series come from the legacy of the earlier, beloved ABAC A29 and A39 pumps. Appreciated for both their sturdiness and ease of use, these pumps have been a must in professionals compressed air for many years. Today, ABAC is proud to bring a breath of fresh air to its iconic, oil lubricated pumps. And in doing so, changing forever the whole field of professional air compressors.

ABAC ZERO pumps deliver you clean, oil-free air. The innovative technology means no oil change and you will not be forced anymore to those lenghty cleaning sessions due to greasy condensate from the tank drain. On top of that, all damages caused by wrong or exhausted oil are avoided. In one fell swoop remove maintenance costs and timely demanding cleaning jobs.



Applications





Orbital sanding



. wrenchina



Hammering



Professional blowing

Clean air

Protect your tools without oil residual



Comfort

With full handle and rubber on the handle

Flexibility

Universal air outlet

Pollution-free, environmentally friendly

The need for condensate treatment is eliminated. This means you can safeguard the environment and better comply with international regulations.

Costs-saving

Lower your budget, raise the income, forget maintenance costs required by oil lubricated air compressors.

Auto-preservation

Oil-free pump doesn't require any oil changes

Easy to move

4 wheels professional line wheel design







Zero oil
Zero pollution
Zero worries

ABAC ZERO pump is the ultimate evolution within single-stage air compressors scenario. Thanks to the advanced materials and components employed in its design **ABAC ZERO** breaks your air free from any oil residual.

The technological switch from oil lubricated air compressors results in the business opportunity offered to professionals to avoid oil change treatments and, at the same time, to comply with International regulations.

In addition, **ABAC ZERO** truly benefits every car repairer, painting specialist and carpenter with its limited maintenance operations. Due to the new oil-free setup, professionals are once for all unfettered by oil refill and change as well as finally being able to work in cleaner environments.





				는		重			-	4		4)	W.	Kg
Model	Part number	L	config.	I/min	Oil	Pump	HP	kW	rpm	Volts	Bar	dB(A)	LxWxH (mm)	kg
PRO A29B-0 27 CM2	4116000266	27	С	255	Oil Free	A29B-0	2	1,5	1075	230/1/50	10	94	863x378x693	43
PRO A29B-0 27 CT2	4116000267	27	С	255	Oil Free	A29B-0	2	1,5	1075	400/3/50	10	94	863x378x693	43
PRO A29B-0 50 CM2	4116000268	50	С	255	Oil Free	A29B-0	2	1,5	1075	230/1/50	10	94	863x413x780	49
PRO A29B-0 50 CT2	4116000269	50	С	255	Oil Free	A29B-0	2	1,5	1075	400/3/50	10	94	863x413x780	49
PRO A29B-0 50 CM3	4116000274	50	С	320	Oil Free	A29B-0	3	2.2	1300	230/1/50	10	96	863x410x776	58
PRO A29B-0 50 CT3	4116000275	50	С	320	Oil Free	A29B-0	3	2.2	1300	400/3/50	10	97	863x410x776	58
PRO A29B-0 100 CM2	4116000270	100	С	255	Oil Free	A29B-0	2	1,5	1075	230/1/50	10	94	1006x488x908	56
PRO A29B-0 100 CT2	4116000271	100	С	255	Oil Free	A29B-0	2	1,5	1075	400/3/50	10	94	1006x488x908	56
PRO A29B-0 100 CM3	4116000276	100	С	320	Oil Free	A29B-0	3	2.2	1300	230/1/50	10	96	1007x488x908	56
PRO A29B-0 100 CT3	4116000277	100	С	320	Oil Free	A29B-0	3	2.2	1300	400/3/50	10	97	1007x488x908	56
PRO A39B-0 100 CM3	4116000284	100	С	393	Oil Free	A39B-0	3	2.2	1050	230/1/50	10	96	1006x488x908	72
PRO A39B-0 100 CT3	4116000285	100	С	393	Oil Free	A39B-0	3	2.2	1050	400/3/50	10	97	1006x488x908	72
PRO A29B-0 150 CM2	4116000272	150	С	255	Oil Free	A29B-0	2	1,5	1075	230/1/50	10	94	1306x501x987	87
PRO A29B-0 150 CT2	4116000273	150	С	255	Oil Free	A29B-0	2	1,5	1075	400/3/50	10	94	1306x501x987	87
PRO A29B-0 150 CM3	4116000278	150	С	320	Oil Free	A29B-0	3	2.2	1300	230/1/50	10	96	1306x501x987	87
PRO A29B-0 150 CT3	4116000279	150	С	320	Oil Free	A29B-0	3	2.2	1300	400/3/50	10	97	1306x501x987	87
PRO A39B-0 150 CM3	4116000286	150	С	393	Oil Free	A39B-0	3	2.2	1050	230/1/50	10	96	1306x501x987	87
PRO A39B-0 150 CT3	4116000287	150	С	393	Oil Free	A39B-0	3	2.2	1050	400/3/50	10	97	1306x501x987	87
PRO A29B-0 200 CM3	4116000280	200	С	320	Oil Free	A29B-0	3	2.2	1300	230/1/50	10	96	1437x573x1039	91
PRO A29B-0 200 CT3	4116000281	200	С	320	Oil Free	A29B-0	3	2.2	1300	400/3/50	10	97	1437x573x1039	91
PRO A39B-0 200 CM3	4116000288	200	С	393	Oil Free	A39B-0	3	2.2	1050	230/1/50	10	96	1437x573x1039	91
PRO A39B-0 200 CT3	4116000289	200	С	393	Oil Free	A39B-0	3	2.2	1050	400/3/50	10	97	1437x573x1039	91
PRO A39B-0 200 CT4	4116000292	200	С	486	Oil Free	A39B-0	4	3	1300	400/3/50	10	97	1500x470x1110	91
PRO A39B-0 270 CM3	4116000290	270	С	393	Oil Free	A39B-0	3	2.2	1050	230/1/50	10	96	1437x573x1039	138
PRO A39B-0 270 CT3	4116000291	270	С	393	Oil Free	A39B-0	3	2.2	1050	400/3/50	10	97	1437x573x1039	138
PRO A39B-0 270 CT4	4116000293	270	С	486	Oil Free	A39B-0	4	3	1300	400/3/50	10	97	1437x573x1039	138



ABAC Air Compressors S.P.A.
VIA CRISTOFORO COLOMBO, 3 – 10070 ROBASSOMERO (TO) ITALY
TEL. +39 011 9246415-421 WWW.ABACAIRCOMPRESSORS.COM

©ABAC 2019
THE CONTENTS OF THIS PUBLICATION ARE THE COPYRIGHT OF THE PUBLISHER AND MAY NOT BE REPRODUCED (EVEN EXTRACTS) UNLESS PRIOR WRITTEN PERMISSION IS GRANTED. EVERY CARE HAS BEEN TAKEN TO ENSURE THE ACCURACY OF THE INFORMATION CONTAINED IN THIS PUBLICATION BUT NO LIABILITY CAN BE ACCEPTED FOR ANY LOSS OR DAMAGE WHETHER DIRECT, INDIRECT OR CONSEQUENTIAL ARISING OUT OF THE USE OF THE INFORMATION CONTAINED HEREIN.

